

EW-LT15 (C)

<i>Technical Specifications</i>		
Model name	EW-LT15(C) LCD Monitor	
LCD Display	15" active matrix TFT XGA LCD	
Active Area	304.128 (H) * 228.096 (V) mm	
Dot Pitch	0.279 (H) * 0.279 (V) mm	
Contrast Ratio	400 : 1	
Brightness	250 cd/m ²	
Response Time	16 ms	
Viewing Angle	Horizontal	120° +/- 10°
	Vertical	100° +/- 10°
Display Color	262144 colors	
PC Interface	15 Pin D-Sub, RGB, 0-0.7Vpp, RGB Analog, 75 Ohm terminated	
Display Mode	VEGA : VGA / SVGA / XGA, MAC ; 640 * 480, 800 * 600	
DVI Interface	Optional	
Max Resolution	1024 * 768	
Horizontal Frequency	31.5 KHz ~ 60 KHz	
Vertical Frequency	56 Hz ~ 75 Hz	
OSD Controls	Contrast; Brightness, Auto adjust, Clock, Phase, H-Position, V-Position, Input...	
Power Adapter	AC Input : 100-240V ~ 1.8A, 50-60Hz DC Output : 12-17V / 4.0A, 12V, DC Input	
Operating Conditions	Temperature : 0°C ~ 50°C, Humidity : 5% ~ 90%.	
Storage Conditions	Temperature : -20°C ~ +60°C, Humidity : 5% ~ 95%.	
Speakers	2W * 2	
Plug & Play	VESA DDC2B	
Certification	CE, FCC(Doc), TUV/GS, UL	
Dimension	Set	340 (H) * 360 (V) * 150 (D) mm
	Packing	410 (H) * 410 (V) * 175 (D) mm
Weight	NW	4.2 Kg
	GW	6.0 Kg
Loading Quantity	20ft	900
	40ft H.Q	1800
(Optional) – TV Tuner : NTSC, Supply V-chip & Closed Caption, Function PAL, Supply Teletex Function, Supply MTS Function.		
(Optional) AV Input / S-Video Input / Audio output / Y Pb Pr Input		
Note: Specifications are subjected to change without prior notice.		