

## EW-LT17(C)

<i>Technical Specifications</i>		
Model name		EW-LT17(C) LCD Monitor
LCD Display		17" active matrix TFT SXGA LCD
Active Area		337.920 (H) * 270.336 (V) mm
Dot Pitch		0.246 (H) * 0.246 (V) mm
Contrast Ratio		400 : 1
Brightness		260 cd/m <sup>2</sup>
Response Time		16 ms
Viewing Angle	Horizontal	160° +/- 10°
	Vertical	140° +/- 10°
Display Color		16.7 M colors
PC Interface		15 Pin D-Sub, RGB, 0-0.7Vpp, RGB Analog, 75 Ohm terminated
Display Mode		VEGA : VGA / SVGA / XGA/SXGA , MAC : 640 * 480, 800 * 600
DVI Interface		Optional
Max Resolution		1280 * 1024
Horizontal Frequency		31.5 KHz ~ 60 KHz
Vertical Frequency		56 Hz ~ 75 Hz
OSD Controls		Contrast; Brightness, Auto adjust, Clock, Phase, H-Position, V-Position, Input...
Power Adapter		AC Input : 100-240V ~ 1.8A, 50-60Hz DC Output : 12-17V / 4.0A, 12V, DC Input
Operating Conditions		Temperature : 0°C ~ 50°C, Humidity : 5% ~ 90%.
Storage Conditions		Temperature : -20°C ~ +60°C, Humidity : 5% ~ 95%.
Speakers		2W * 2
Plug & Play		VESA DDC2B
Certification		CE, FCC(Doc), TUV/GS, UL
Dimension	Set	410 (H) * 410 (V) * 170 (D) mm
	Packing	470 (H) * 478 (V) * 202 (D) mm
Weight	NW	4.2 Kg
	GW	6.0 Kg
Loading Quantity	20ft	512
	40ft H.Q	1024
(Optional) – TV Tuner : NTSC, Supply V-chip & Closed Caption, Function PAL, Supply Teletex Function, Supply MTS Function.		
(Optional) AV Input / S-Video Input / Audio output / Y Pb Pr Input		
Note: Specifications are subjected to change without prior notice.		