

EW-LT20

<i>Technical Specifications</i>		
Model name		EW-LT20 LCD Monitor
LCD Display		20" active matrix TFT UXGA LCD
Active Area		408 (H) * 306 (V) mm
Dot Pitch		0.255 (H) * 0.255 (V) mm
Contrast Ratio		800 : 1
Brightness		300 cd/m ²
Response Time		8 ms
Viewing Angle	Horizontal	170° +/- 10°
	Vertical	170° +/- 10°
Display Color		16.7M colors
PC Interface		15 Pin D-Sub, RGB, 0-0.7Vpp, RGB Analog, 75 Ohm terminated
Display Mode		VEGA : VGA / SVGA / XGA / SXGA / WXGA+ / UXGA , MAC ; 640 * 480, 800 * 600
DVI Interface		Optional
AV Interface		Optional
TV Interface		Optional
Max Resolution		1600 * 1200
Horizontal Frequency		31.5 KHz ~ 93.8 KHz
Vertical Frequency		60 Hz ~ 75 Hz
OSD Controls		Contrast, Brightness, Auto adjust, Clock, Phase, H-Position, V-Position, Input...
Power Adapter		AC Input : 100-240V ~ 1.8A, 50-60Hz DC Output : 12-17V / 5.0A, 12V, DC Input
Operating Conditions		Temperature : 0°C ~ 50°C, Humidity : 5% ~ 90%.
Storage Conditions		Temperature : -20°C ~ +60°C, Humidity : 5% ~ 95%.
Speakers		3W * 2
Plug & Play		VESA DDC2B
Certification		CE, FCC(Doc), TUV/GS, UL
Dimension	Set	568 (H) * 447 (V) * 150 (D) mm
	Packing	625 (H) * 505 (V) * 182 (D) mm
Weight	NW	7.0 Kg
	GW	9.5 Kg
Loading Quantity	20ft	900
	40ft H.Q	1800
(Optional) – TV Tuner : NTSC, Supply V-chip & Closed Caption, Function PAL, Supply Teletex Function, Supply MTS Function.		
(Optional) AV Input / S-Video Input / Audio output / Y Pb Pr Input		
Note: Specifications are subjected to change without prior notice.		