

TW-2602B

<i>Technical Specifications</i>		
Model name	TW-2602B LCD Monitor	
LCD Display	26" active matrix TFT SXGA LCD	
Active Area	575.769 (H) * 323.712 (V) mm	
Dot Pitch	0.4215 (H) * 0.4215 (V) mm	
Contrast Ratio	800 : 1	
Brightness	500 cd/m ²	
Response Time	8 ms	
Viewing Angle	Horizontal	160° +/- 10°
	Vertical	160° +/- 10°
Display Color	16.7M colors	
External connections	15 pin D-sub x1 , PC Audio-in Phone jack x1 RCA Video-in x2, S Video-in x1 RCA Audio-out x1	
Display Mode	VEGA : VGA SVGA XGA / SXGA / WXGA, MAC : 640 * 480, 800 * 600	
Max Resolution	1280 * 1024	
Horizontal Frequency	31.5 KHz ~ 60 KHz	
Vertical Frequency	56 Hz ~ 75 Hz	
OSD Controls	Contrast, Brightness, Auto adjust, Clock, Phase, H-Position, V-Position, Input...	
Power Adapter	AC Input : 100-240V ~ 1.8A, 50-60Hz DC Output : 12-17V / 4.0A, 12V, DC Input	
Operating Conditions	Temperature : 0°C ~ 50°C, Humidity : 5% ~ 90%.	
Storage Conditions	Temperature : -20°C ~ +60°C, Humidity : 5% ~ 95%.	
Speakers	5W * 2	
Plug & Play	VESA DDC2B	
Certification	CE, FCC(Doc), TUV/GS, UL	
Dimension	Set	
	Packing	
Weight	NW	
	GW	
Loading Quantity	20ft	
	40ft H.Q	
(Optional) – TV Tuner : NTSC, Supply V-chip & Closed Caption, Function PAL, Supply MTS Function.		
(Optional) AV Input / S-Video Input / Audio output / Y Pb Pr Input		
Note: Specifications are subjected to change without prior notice.		